

## IW-RS104-02M

### =Motherboard=

Brand	Model	CPU Socket	Form Factor
Asrockrack	EP2C612D16C-4L	Socket-2011	EEB12"x13"
Asrockrack	EP2C612D16-2L2T	Socket-2011	EEB12"x13"
Asrockrack	C236M-WS	Socket-1151	ATX-UP
Supermicro	X10DRL-I	Socket-2011	ATX-DP
Supermicro	X10SRL-F	Socket-2011	ATX-UP

### =Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
WD	WD5000BPKX	SATA 3	2.5"	500GB	7200
Seagate	ST336754SS	SAS 3G	3.5"	36GB	15000
Seagate	ST8000NM0075	SAS 12G	3.5"	8TB	7200
Toshiba	PX02SMF020-SSD	SAS 12G	2.5"	200GB	SSD
HGST	HUC156030CSS200	SAS12G	2.5"	300GB	15000

### =Power Supply=

Brand	Model	Output Watt	80+ Level	Form Factor
Acbel	EP1A5501B	550W	Gold	Single
PowerOne	SPSINWN-04GS313	750W	Platinum	Redundant

### =RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9260-8i	Internal x8	SATA/SAS 6G	0,1,5,6,10,50,60
LSI	9271-8i	Internal x8	SATA/SAS 6G	0,1,5,6,10,50,60
Intel	C236 onboard SATA RAID	Internal x8	SATA III	0,1,5,10

### =Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	T318A	1U	Socket-2011	165W

#### Note:

- \* The listed components had been tested by In Win lab according to In Win's verification standard.
- \* To avoid failure and errors, please also reference components vendors' user manual.
- \* The actual performance is affected by host's hardware specification, software, file system, and other conditions.