

IW-RJ424-04

4U JBOD



Features & Benefits

- Supports SAS 12G / SATA 6G via dual / single expander
- GUI supports via Ethernet board (Optional)
- Tool-less design for 3.5-inch HDD carrier
- Designed for high scalability and high availability in storage applications
- Supports SES-2 (SCSI Enclosure Service)
- Low maintenance and serviceable with FRU designed for expander / fan / power supplies
- Fixed rail included (Optional tool-less sliding rail)
- Supports high efficiency CRPS power supplies

Specifications

Standard	EIA-RS310D
Dimensions (D x W x H) w/o Front Door	520.7 x 482.6 x 176 mm (20.5" x 19" x 7")
Storage	External: Hot-swap 3.5" x 24 (SAS 12Gbps)
Maximum Capacity (per enclosure)	Up to 192TB (Cascades to 3 enclosures with 72 HDDs, including 1 host server)
Power Supply	Supports <ul style="list-style-type: none"> ▪ Form Factor: Platinum CRPS redundant ▪ Watt: 550W
Cooling Fan	8038mm x 4
12G Expander Module	1 or 2
Host/Expansion port	3 x Mini SAS HD (SFF-8644) for each 12G expander module
Management	Smart fan, thermal monitor, HDD monitor, voltage monitor, alarm warning
SES	Supports SES-2 (SCSI Enclosure Service)
Maintenance	Supports Management by Ethernet (Optional) and RS-232
HDD Power Management	HDD sequential power on
Temperature	0°C to 35°C
Material	Material: SGCC Thickness: 1.0 mm
Rail Kit	Fixed rail included. (Optional 30" tool-less & ball-bearing slide rail)

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make any final modifications.

* The above image is for reference only. All hardware components are not included.



CONTEMPORARY & INNOVATIVE
www.in-win.com