

# IW-RJ316-04

3U JBOD



## Features & Benefits

- Supports SAS 12G / SATA 6G via dual / single expander
- GUI supports via Ethernet board (Optional)
- Tool-less design for 3.5-inch HDD carrier
- Designed for high scalability and high availability in storage applications
- Supports SES-2 (SCSI Enclosure Service)
- Low maintenance and serviceable with FRU designed for expander / fan / power supplies
- Fixed rail included. (Optional tool-less sliding rail)
- Supports high efficiency CRPS power supplies

## Specifications

<b>Standard</b>	EIA-RS310D
<b>Dimensions (D x W x H) w/o Front Door</b>	520.7 x 482.6 x 131 mm (20.5" x 19" x 5.25")
<b>Storage</b>	External: Hot-swap 3.5" x 16 (SAS 12Gbps)
<b>Maximum Capacity (per enclosure)</b>	Up to 128 TB (Cascades to 3 enclosures with 48 HDDs, including 1 host server)
<b>Power Supply</b>	Supports <ul style="list-style-type: none"> <li>▪ Form Factor: Platinum CRPS redundant</li> <li>▪ Watt: 550W</li> </ul>
<b>Cooling Fan</b>	8038mm x 4
<b>12G Expander Module</b>	1 or 2
<b>Host/Expansion port</b>	3 x Mini SAS HD (SFF-8644) for each 12G expander module
<b>Management</b>	Smart fan, thermal monitor, HDD monitor, voltage monitor, alarm warning
<b>SES</b>	Supports SES-2 (SCSI Enclosure Service)
<b>Maintenance</b>	Supports Management by Ethernet (Optional) and RS-232
<b>HDD Power Management</b>	HDD sequential power on
<b>Temperature</b>	0°C to 35°C
<b>Material</b>	Material: SGCC Thickness: 1.0 mm
<b>Rail Kit</b>	Fixed rail included. (Optional 20" tool-less & ball-bearing slide rail)

\* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make any final modifications.

\* The above image is for reference only. All hardware components are not included.



CONTEMPORARY & INNOVATIVE  
www.in-win.com