

INWIN

600W - 700W - 800W

100-240Vac, 50-60Hz

ATX 12V V2.31 / EPS 12V V2.92 Version

DESERT FOX COMMANDER III

Features :

- ✘ **Modularized Cable Management**
- ✘ **8(6+2) Pin PCI-E Connectors for Multi-GPU Graphic Cards**
- ✘ **Four Independent +12V Outputs**
- ✘ **+5V and +3.3V DC to DC Design**
- ✘ **Intelligent Fan Speed Control for Optimal Acoustic**
- ✘ **135mm Double Ball-Bearing Ultra Long-Life Fan**
- ✘ **Patented 4 Pin Molex Easy-Swap Connectors**
- ✘ **Independent +12V Feedback Circuit Design for Improved Reliability**
- ✘ **105°C High-Quality Japanese Bulk Capacitor Ensures Reliability and Superior Performance**
- ✘ **Multiple Output Protector: OCP, OVP, OPP, UVP and SCP**
- ✘ **3 oz Copper PCB: Lower Impedance Increases Efficiency and Electrical Current Flow**
- ✘ **Full Range Active Power Factor Correction (PF>0.99)**
- ✘ **Supports the Latest ATX12V V2.31 & EPS12V V2.92**
- ✘ **MTBF>120,000 Hours**
- ✘ **ErP Lot 6 Compliant**



Supports PCIe



Ball B



ErP Lot 6



LOW NOISE



3.5OZ



MODULARIZED CABLE



HIGH EFFICIENCY



NVIDIA SLI



CONTEMPORARY & INNOVATIVE IN WIN

www.inwin-style.com





DESERT FOX COMMANDER III



800W



700W



600W



+5V and +3.3V DC to DC Design



105°C High-Quality Japanese Bulk Capacitor



135mm Double Ball-Bearing Fan



Modularized Cable Management



6+2 Pin PCI-E

Specifications

Model No.	AC Input	Max. DC Output Current											
		+3.3V	+5V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB	MAX1	MAX2	MAX3	Total Power
COMMANDER600 III	100V-240Vac, 50-60Hz, 8A	24A	24A	25A	25A	25A	25A	0.3A	3A	120W	590W	18.6W	600W
COMMANDER700 III	100V-240Vac, 50-60Hz, 9A	24A	24A	25A	25A	25A	25A	0.3A	3A	120W	690W	18.6W	700W
COMMANDER800 III	100V-240Vac, 50-60Hz, 10A	24A	24A	25A	25A	25A	25A	0.3A	3A	120W	790W	18.6W	800W

MAX1: +3.3V, +5V Total Output ; MAX2: +12V Total Output ; MAX3: -12V, +5VSB Total Output

Type	ATX 12V 2.31 / EPS 12V 2.92 Version
PFC	Full Range Active PFC (PF>0.99)
Fan	Silent 135mm Double Ball-Bearing Fan
Efficiency	Up to 90%
MTBF	> 120,000 Hours
Full Protection	OVP / OCP / OPP / UVP / SCP
Dimensions (W x L x H)	150 x 160 x 86 mm

Connectors

					
20+4 Pin Motherboard Connector	8(4+4) Pin ATX/EPS +12V CPU Connector	4 Pin Molex Easy-Swap Peripheral Connector	Serial ATA (SATA) Connector	4 Pin Floppy Connector	8(6+2) Pin PCI-Express Connector
X 1	X 1	X 3	X 9	X 1	X 4

