



www.in-win.com

HF Series

TFX 12V V2.31

Features

- Multiple +12V Output
- Smart Thermal Control to Balance Noise & Cooling
- 80mm Cooling Fan
- MTBF 100KHRs @ 25°C per MIL-STD-217D/F
- Operating Ambient +10°C Minimum to +50°C Maximum
- Meets Intel® Haswell Processors
- ErP Lot 6 Compliant

Safety



Dimensions

85(W) X 175(L) X 65(H) mm



Specifications

Model No.	Max. Output	AC Input	PFC	Max. Output Current								
				+12V1/ Peak	+12V2/ Peak	+5V	+3.3V	-12V	5VSB/ Peak	MAX1	MAX2	MAX3
IP-P300HF7-2	300W	100-240V	Active	18/20A	18/20A	16A	16A	0.3A	3/3.5A	90W	276W	300W

* MAX1: 5V & 3.3V Total Output

* MAX2: +12V Total Output

* MAX3: Total Output Power

Connectors

Model No.						
Qty.	IP-P300HF7-2	1	1	1	3	
		24 Pin Main Power Connector	4+4 Pin +12V CPU Power Connector	4 Pin FDD Power Connector	Peripheral Power Connector	SATA Power Connector

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.