

## IW-RS208-02M

### =Motherboard=

Brand	Model	CPU Socket	Form Factor
Supermicro	X10DRL-I	Socket-2011	ATX-DP
Supermicro	X10DAC	Socket-2011	EEB 12"x13"
Asrockrack	EP2C612D16C-4L	Socket-2011	EEB 12"x13"
Intel	S1200SPL	Socket-1151	uATX

### =Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
Seagate	ST9250610NS	SATA 3	2.5"	250GB	7200
Seagate	ST1500DL003	SATA 3	3.5"	1.5TB	7200
Seagate	ST3300657SS	SAS 6G	3.5"	300GB	15000
Seagate	ST336754SS	SAS 3G	3.5"	36GB	15000

### =Power Supply=

Brand	Model	Output Watt	80+ Level	Form Factor
Zippy	M1P2-5500V4V	500W	Silver	Redundant
ACBEL	R2IS7651A	650W	Platinum	Redundant

### =RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9260-8i	Internal x8	SATA/SAS 6G	0,1,5,6,10,50,60

### =Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
DYNATRON	R14	Narrow	Socket-2011	150W

Note:

- \* The listed components had been tested by In Win lab according to In Win's verification standard.
- \* To avoid failure and errors, please also reference components vendors' user manual.
- \* The actual performance is affected by host's hardware specification, software, file system, and other conditions.