

IW-RS208-03

2U Storage Rackmount Server



Features & Benefits

- Tray Less design for 3.5 inch HDD carrier.
- State-of-the-art performance and scalability.
- Supports SES-2 (SCSI Enclosure Service)
- Adjustable Thermal system.
- Tool-less Sliding Rail support.
- CRPS power module support for all series.

Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX (12" x 9.6"); ATX(12" x 10"); EEB(12" x 13")
Dimensions (D x W x H) w/o Front Door	660.4 x 438 x 87 mm (26" x 17" x 3.5")
Drive Bay	External: Hot-Swap 3.5" x 8 Internal: 2.5" HDD x 2 or Rear 2.5" Hot-Swap for OS (SSD 7mm) x 2 (Optional)
Power Supply	Supports <ul style="list-style-type: none"> ▪ Form Factor: Platinum CRPS Redundant ▪ Watt: 800W
Indicator	Power LED, LAN1/LAN2/LAN3/LAN4 LED, System LED, ID LED
Front Control Panel	Power on/off, Reset, NMI, ID SW, USB3.0 x1, Mute button
Backplane	MINI SAS HD /12Gb/s without expander
Cooling Fan	Supports 8038mm PWM Fan x3, 4028mm Fan x2 Modularize design with anti-vibration
Expansion Slot	Low-Profile PCI Slot x 7
Material	Material: SGCC Thickness: 1.0 mm
Slide Rail	Support 28" screwless slide rail, Ball-bearing

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.

* Above image for reference only. All hardware components are not included.



CONTEMPORARY & INNOVATIVE
www.in-win.com