

IW-RS110-02M

1U Storage Rackmount Server Chassis



Features & Benefits

- 1U rack-mount middle depth chassis
- External 2.5" x 10 hot-swap HDD trays supported
- Easy-swap 40 mm PWM fans with Anti-Vibration mechanism
- Supports 12Gb/s Mini-SAS HD backplane
- Iron front panel with silver coating



Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX (12" x 9.6"), ATX (12" x 10"), EEB (12" x 13")
Dimensions (D x W x H) w/o Front Door	625 x 482.6 x 44.4 mm (24" x 19" x 1.75")
Drive Bay	External: Hot-Swap 2.5" x 10
Power Supply	Supports <ul style="list-style-type: none"> ▪ Form Factor: Single or 1U 1+1 Redundant ▪ Watt: Single 500W, Redundant up to 750W
Indicator	Power Status, HDD, LANs
Front Control Panel	Power Switch, System Reset, USB 3.0 x 1
Backplane	<ul style="list-style-type: none"> ▪ SATA (6Gb/s Supported) ▪ Mini-SAS (6Gb/s Supported) ▪ Mini SAS HD(12G/s Supported)
Cooling Fan	Supports 40 mm (Up to T= 56 mm) PWM Easy-Swap Fan x 6
Expansion Slot	Full Height PCI Slot x 1 (via riser card and bracket)
Material	Material: SGCC Thickness: 1.0 mm
Rail Kit	Support 28" screwless slide rail, Ball-bearing
Packaging Dimensions (D x W x H)	700 x 570 x 180 mm
Shipping Information	Net Weight: 5.9 kg Gross Weight: 9.4 kg Container Info <ul style="list-style-type: none"> ▪ Single Packing with pallets: 20': 216pcs, 40': 468pcs, 40'H: 572pcs

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.

* Above image for reference only. All hardware components are not included.

