

IW-R300-02N

Open-Bay 3U Server Chassis



Features & Benefits

- Compatible with single or redundant power supply
- Expandable storage option with two In Win storage kits
- Supporting two rear fan to optimize thermal exhaust efficiency
- Lockable front door for hardware security
- Specially designed for surveillance DVR composition



Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX (12" X 9.6"), CEB (12" X10.5"), EEB(12" X 13")
Dimensions (D x W x H) w/o Front Door	660 x 482.6 x 133.4 mm (26" x 19" x 5.25")
Drive Bay	External: 5.25" x 4, 2.5" Hot-swap x 2 (Optional) Internal: 2.5" X 1
Power Supply	Supports ▪ Form Factor: 1U or 2U Single , CRPS 1+1 Redundant ▪ Watt: Single 500W , CRPS 550W/800W/1200W
Front Control Panel	Button: Power On/Off, NMI, Reset, ID SW Indicator: Power LED, ID LED, System LED, LAN1/LAN2/LAN3/LAN4 LED
Chassis Security	Intrusion Switch
Cooling Fan	▪ 80mm PWM Middle Fan x 3 ,up to 4 ▪ 60 x 25 mm PWM Rear Fan x 2 (Optional)
Expansion Slot	Full Height PCI Slot x 7
Material	Material: SGCC Thickness: 1.2 mm
Rail Kit	Rail Kit Support 28" tool-less slide rail, Ball-bearing

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make any final modifications.

* The above image is for reference only. All hardware components are not included.



IN WIN

CONTEMPORARY & INNOVATIVE

www.in-win.com