





Features & Benefits

- Flexible drive bays configuration for ODD, 2.5" and 3.5" HDD
 - Supports easy-swap rear fan x 2 for upgrade
- Compatible with standard PS2 or mini-redundant power supply
 - Expandable storage option with InWin storage kits
- GPU holder and adjustable card retainer supporting 350mm dual-slot PCIe cards x 4
 - Convertible to tower with chassis stands (optional)
 - Lockable front door for data security
- Tool-free cover for easy installation and quick maintenance



Specifications

Industry Standard	Compatible with EIA-RS310D standard 19" cabinets
M/B Form Factor	ATX (12" x 9.6"), CEB (12" x 10.5")
Drive Bay	• External: 5.25" x 3, 3.5" x 1 • Internal: 3.5" x 3, or 3.5" x 2 & 2.5" x 1
Power Supply	Supports: • PS2 single PSU • 550W/800W/1200W/1600W 1+1 CRPS 80 Plus Platinum
Indicators	Power status, HDD, LAN activity LEDs
Front Control Panel	Power switch, system reset, USB 2.0 x 2
Chassis Security	Intrusion switch (optional)
Cooling Fans	• 120 x 25mm PWM front fan x 1, 3500RPM • 80 x 25mm PWM rear fan x 2 (optional), 4200RPM • 80 x 25mm PWM rear fan x 2 (optional), 4500RPM
Expansion Slot	Full height PCIe slots x 8
Material	• Material: SGCC • Thickness: 1.2mm
Rail Kit	Supports 28" tool-less & ball-bearing slide rails
Product Dimensions (DxWxH; Chassis Only)	515x 430 x 174.8mm (20.3" x 16.9" x 6.9")
Package Dimensions (DxWxH)	696 x 610 x 310mm
Weight (Chassis Only)	• Net weight: 11.5kg • Gross weight: 14.7kg
Cubic Feet	4.65
Container Information	Single packing with pallets: • 20': 144pcs • 40': 300pcs • 40' HQ: 350pcs



Optional Items

Item	Part Number	Description	Support
Slide Rail	3RAMIS129500	28" tool-less & ball-bearing slide rails (weight capacity 35kg)	1 set
Power Supply	3RAMAP025102	80 Plus Platinum 550W CRPS	Max. 2
Power Supply	3RAMAP025202	80 Plus Platinum 800W CRPS	Max. 2
Power Supply	3RAMAP026501	80 Plus Platinum CRPS 1200W (AC input 100-127V, total power 800W max. / AC input 200-240V, total power 1200W max.)	Max. 2
Power Supply	3RAMAP044300	80 Plus Platinum CRPS 1600W (AC input 100-127V, total power 1000W max. / AC input 200-240V, total power 1600W max.)	Max. 2
Power Supply	3RAMAP042300	PDB power cage for CRPS Max. 1200W, Short Type	1
Power Supply	3RAMAP027201	PDB power cage for CRPS Max. 1200W	1
Power Supply	3RAMAP030501	PDB power cage for CRPS Max. 1600W	1
Fan	3RAMFB014500	120 x 25mm front fan, PWM, 3500RPM	1
Fan	3RAMFB015300	80 x 25mm rear fan, PWM, 4200RPM	2
Fan	3RAMFB014800	80 x 25mm rear fan, PWM, 4500RPM	2
Storage Kit	2RAKID044201	IW-SK23-02, 3.5" hot-swap HDD x 3, SAS/SATA 12Gb/s	1
Storage Kit	2RAKID073901	IW-SK34-02, 3.5" hot-swap HDD x 4, SAS/SATA 12Gb/s	1
Storage Kit	2RAKID088302	IW-SK23-07, 3.5" hot-swap HDD x 3, SAS/SATA 12Gb/s	1
Storage Kit	2RAKID088403	IW-SK34-07, 3.5" hot-swap HDD x 4, SAS/SATA 12Gb/s	1
Others	3RAMRW011300	Intrusion switch / 800mm	1
Others	2RALXX396100	Foot stands	1 set

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make any final modifications.

* The above image is for reference only. All hardware components and optional parts are not included.