

IW-RS208-07

=Motherboard=

Brand	Model	CPU Socket	Form Factor
Supermicro	X11DPH-i	Socket-3647	EEB
Supermicro	MBD-X13DEI	Socket-4677	EEB
ASROCKRACK	SP2C741D16-2T	Socket-4677	EEB

=CPU=

Brand	Model	CPU Socket	Form Factor	TDP
Intel®	Xeon® scalable 6150	Socket-3647	Purley	165W
Intel®	Xeon® Gold 6438Y+	Socket-4677	Eagle Stream	205W
Intel®	Xeon® Gold 6444Y+	Socket-4677	Eagle Stream	270W

=Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
Intel®	P750 800GB SSD	NVMe	2.5" 25W	800GB	--
KingStone	SEDC100M/3840G	Nvme	2.5"	3.84TB	--
WD	HUS726T6TAL5204	SAS	3.5"	6TB	7200RPM
Seagate	ST12000NM0038	SAS	3.5"	12TB	7200RPM
Seagate	EXOS 7E10	SAS	3.5"	4TB	7200 RPM
Seagate	EXOS 7E8	SAS	3.5"	4TB	7200RPM

=RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x 8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9460-16i	Internal x 4 NVMe	SATA/SAS 12G	0,1,5,6,10,50,60

=Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	B5	Purley Narrow	Socket-3647	205W
Dynatron	S5R1	Eagle Stream	Socket-4677	270W

=Power Supply=

Brand	Model	Form Factor	Wattage
IW	R2CU6801A	CRPS	800W
IW	R1CA2801A	CRPS	800W

Note:

- * The listed components had been tested by InWin lab according to InWin's verification standard.
- * To avoid failure and errors, please also refer to components' vendors' user manual.
- * The actual performance is affected by host's hardware specification, software, file system, and other conditions.