



www.in-win.com

CN Series

SFX 12V V3.21

Features

- Multiple +12V Output
- Smart Thermal Control to Balance Noise & Cooling
- 80mm Cooling Fan
- MTBF 100Khrs @ 25°C per MIL-STD-217D/F
- Operating Ambient +10°C Minimum to +50°C Maximum
- Meets Intel® Haswell Processors
- ErP Lot 6 Compliant

Safety



Dimensions

125(W) X 100(L) X 63.5(H) mm



Specifications

Model No.	Max. Output	AC Input	PFC	Max. Output Current								
				+12V1/ Peak	+12V2/ Peak	+5V	+3.3V	-12V	5VSB/ Peak	MAX1	MAX2	MAX3
IP-P300CN7-2	300W	100-240V	Active	11/13A	8/13A	15A	21A	0.3A	2/2.5A	103W	228W	300W

* MAX1: 5V & 3.3V Total Output

* MAX2: +12V Total Output

* MAX3: Total Output Power

Connectors

Model No.						
		24 Pin Main Power Connector	4+4Pin +12V CPU Power Connector	4 Pin FDD Power Connector	Peripheral Power Connector	SATA Power Connector
Qty.	IP-P300CN7-2	1	1	1	1	3

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.